

S6-GR1P(0.7-3.6)K-M

Solis Single Phase Grid-Tied Inverters

Features:

- Max. efficiency 97.3%
- Wide voltage range and low startup voltage
- Supports export power control
- AFCI protection, proactively reduces fire risk
- 24-hour load consumption monitoring
- Adaptive weak grid

Models:

S6-GR1P0.7K-M / S6-GR1P1K-M

S6-GR1P1.5K-M / S6-GR1P2K-M

S6-GR1P2.5K-M / S6-GR1P3K-M

S6-GR1P3.6K-M



360° View

DATASHEET

Models	0.7K	1K	1.5K	2K	2.5K	3K	3.6K
Input DC							
Recommended max. PV power	1.1 kW	1.5 kW	2.3 kW	3 kW	3.8 kW	4.5 kW	5.4 kW
Max. input voltage	550 V						
Rated voltage	200 V			330 V			
Start-up voltage	60 V			90 V			
MPPT voltage range	50 - 500 V			80 - 500 V			
Max. input current	14 A						19 A
Max. short circuit current	22 A						24 A
MPPT number / Max. input strings number	1 / 1						1 / 2
Output AC							
Rated output power	0.7 kW	1 kW	1.5 kW	2 kW	2.5 kW	3 kW	3.6 kW
Max. apparent output power	0.77 kVA	1.1 kVA	1.65 kVA	2.2 kVA	2.75 kVA	3.3 kVA	3.6 kVA
Max. output power	0.77 kW	1.1 kW	1.65 kW	2.2 kW	2.75 kW	3.3 kW	3.6 kW
Rated grid voltage	1/N/PE, 220 V / 230 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	3.2 A / 3.0 A	4.5 A / 4.3 A	6.8 A / 6.5 A	9.1 A / 8.7 A	11.4 A / 10.9 A	13.6 A / 13 A	16 A
Max. output current	4.4 A	5.2 A	8.1 A	10.5 A	13.3 A	15.7 A	16 A
Power factor	> 0.99 (0.8 leading - 0.8 lagging)						
THDi	< 3%						
Efficiency							
Max. efficiency	96.6%		96.6%	97.1%	97.1%		97.3%
EU efficiency	95.3%		95.4%	96.4%	96.7%		96.8%
Protection							
DC reverse-polarity protection	Yes						
Short circuit protection	Yes						
Output over current protection	Yes						
Surge protection	Yes						
Grid monitoring	Yes						
Anti-islanding protection	Yes						
Temperature protection	Yes						
Multi peak scan	Yes						
Integrated AFCI 2.0	Optional						
Integrated DC switch	Yes						
General Data							
Dimensions (W × H × D)	310 × 373 × 160 mm						
Weight	7.7 kg			8 kg			8.1 kg
Topology	Transformerless						
Self-consumption (night)	< 1 W						
Operating ambient temperature range	-25 ~ +60°C						
Relative humidity	0 - 100%						
Ingress protection	IP66						
Noise emission (typical)	< 20 dB(A)						
Cooling concept	Natural cooling						
Max. operation altitude	4000 m						
Grid connection standard	G98 or G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1, VDE 0126/UTE C 15/VFR:2019, RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA						
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4						
Features							
DC connection	MC4 connector						
AC connection	Quick connection plug						
Display	LCD						
Communication	RS485, Optional: Wi-Fi, GPRS						