

STAR Pro SERIES N-TOPCon 144-cell MODULE

EG-NT72-HLV

580~610W

0~3% POSITIVE TOLERANCE

KEY FEATURES



SMBB cell design

Super multi Busbar cells bring lower resistance and increased Busbar reflectance ensures higher power output



Low degradation

Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance



High Reliability

Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified



Excellent Low-light Performance

Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments




PID Resistant

Excellent PID resistance performance optimized by unique structural design

LINEAR PERFORMANCE WARRANTY


15 Year Product Warranty **30** Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-NT72-HLV

Engineering Drawings



I-V Curves(590W)



Packing Configuration

Pieces per Pallet	36
Size of Packing (mm)	2320*1135*1255
Weight of Packing (kg)	1022
Pieces per Container	720
Size of Container	40' HC

Electrical Characteristics(STC)

Test uncertainty for Pmax: ±3%

Power Level	580	585	590	595	600	605	610
Pmax (W)	580	585	590	595	600	605	610
Vmp (V)	42.53	42.71	42.88	43.06	43.22	43.39	43.56
Imp (A)	13.64	13.70	13.76	13.82	13.89	13.95	14.01
Voc (V)	51.30	51.45	51.62	51.80	51.95	52.10	52.25
Isc (A)	14.43	14.49	14.55	14.61	14.68	14.74	14.80
Module Efficiency (%)	22.5	22.6	22.8	23.0	23.2	23.4	23.6
Maximum System Voltage (V)	1500						
Fuse Rating (A)	25						
Temperature Coefficient Pmax (%/°C)	-0.29						
Temperature Coefficient Isc (%/°C)	0.046						
Temperature Coefficient Voc (%/°C)	-0.24						

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Working Characteristics

Power Level	580	585	590	595	600	605	610
Pmax (W)	436	441	445	449	453	457	461
Vmp (V)	39.61	39.88	40.06	40.23	40.39	40.56	40.73
Imp (A)	11.01	11.06	11.11	11.16	11.22	11.27	11.32
Voc (V)	48.41	48.55	48.70	48.85	49.00	49.15	49.30
Isc (A)	11.65	11.70	11.75	11.81	11.97	12.03	12.09
Power Tolerance (%)	0~+3						
NOCT (°C)	44 ± 2						

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of Cells	144pcs
Size of Cell (mm)	182*91 & 182.2*91.875
Type of Cell	N-type Mono
Front Glass (mm)	3.2
Type of Frame	Anodized aluminum alloy
Junction Box	IP68
Size of Module (mm)	2278*1134*30
Weight (kg)	27
Cables/Connectors	4mm², MC4 compatible
Length of Cable	+300mm/-300mm (connector included)

Remark: customized frame color and cable length available upon request

Maximum Ratings

Operating Temperature (°C)	-40~85
Operating Humidity (%RH)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in March 2026 1st Edition*

CAUTION: All rights and explain reserved by EGING PV.
Specifications included in this datasheet are subject to change without notice.
The specific content of the product warranty refers to EGING's latest warranty.



Tel: 86-519-82585880
Zip: 213213
Add: No.18, Jinwu Road, Jintan Dist,
Changzhou City, Jiangsu Province.
Email: marketing@egingpv.com
Web: www.egingpv.com