




ZXM7-SH132 Series

10BB HALF-CELL Monocrystalline PERC PV Module

490-510W

POWER RANGE

21.48%

MAXIMUM EFFICIENCY

0.55%

YEARLY DEGRADATION



12 YEARS PRODUCT WARRANTY




25 YEARS OUTPUT GUARANTEE

12 years product warranty for general application

15 years product warranty for Rooftop PV system

25 years output warranty / 0.55% Annual Degradation over 25 years



*Please check the valid version of Limited Product Warranty which is officially released by ZNSHINE PV-TECH Co.,Ltd.



IEC 61215/IEC 61730

ISO 14001: Environmental Management System

ISO 9001: Quality Management System

ISO45001: Occupational Health and Safety Management System

*As there are different certification requirements in different markets, please contact your local znshine sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

KEY FEATURES



Excellent Cells Efficiency

MBB technology reduce the distance between busbars and finger grid line which is benefit to power increase.



Better Weak Illumination Response

More power output in weak light condition, such as haze, cloudy, and early morning.



TIER 1


Global, Tier 1 bankable brand, with independently certified advanced automated manufacturing.



Excellent Quality Management System

Warranted reliability and stringent quality assurances well beyond certified requirements.

DIMENSIONS OF PV MODULE(mm)




Front View


Back View

*Remark: customized frame color and cable length available upon request

I-V CURVES OF PV MODULE(490W)



P-V CURVES OF PV MODULE(490W)



ELECTRICAL CHARACTERISTICS | STC*

Module Type	ZXM7 SH132-490/M	ZXM7 SH132-495/M	ZXM7 SH132-500/M	ZXM7 SH132-505/M	ZXM7 SH132-510/M
Nominal Power Watt Pmax(W)*	490±5	495±5	500±5	505±5	510±5
Maximum Power Voltage Vmp(V)	37.70	37.90	38.10	38.30	38.50
Maximum Power Current Imp(A)	13.00	13.07	13.13	13.19	13.25
Open Circuit Voltage Voc(V)	45.30	45.50	45.70	45.90	46.0
Short Circuit Current Isc(A)	13.72	13.78	13.84	13.90	13.97
Module Efficiency (%)	20.64	20.85	21.06	21.27	21.48

*The data above is for reference only and the actual data is in accordance with the practical testing
*STC (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25±2°C, AM 1.5
*Measuring uncertainty: ±3%, all the electrical characteristics such as Power, Im, Vm and FF are within ±3% tolerance.

MECHANICAL DATA

Solar cells	Mono PERC
Cells orientation	132 (6×22)
Module dimension	2094×1134×35 mm (With Frame)
Weight	25.5±1.0 kg
Glass	3.2mm, High Transmission, AR Coated Tempered Glass
Junction box	PV-XT1609Nxyz, IP 68, 3 diodes
Cables	H122Z2-K 1×4,0mm²
Connectors*	PV-XT101.1 Suzhou Xtong Photovoltaic Technologies Co., Ltd. manufactured in china

*Please refer to regional datasheet for specified connector

ELECTRICAL CHARACTERISTICS | NMOT

Maximum Power Pmax(Wp)	366.20	370.0	373.60	377.20	380.80
Maximum Power Voltage Vmpp(V)	35.10	35.30	35.50	35.70	35.90
Maximum Power Current Imp(A)	10.43	10.48	10.52	10.57	10.61
Open Circuit Voltage Voc(V)	42.30	42.50	42.70	42.90	43.00
Short Circuit Current Isc(A)	11.08	11.13	11.18	11.23	11.27

*NMOT: Irradiance 800W/m², Ambient Temperature 20°C, AM 1.5, Wind Speed 1m/s

TEMPERATURE RATINGS

NMOT	44°C ±2°C	Maximum system voltage	1500 V DC
Temperature coefficient of Pmax	-0.35%/°C	Operating temperature	-40°C~+85°C
Temperature coefficient of Voc	-0.29%/°C	Maximum series fuse	25 A
Temperature coefficient of Isc	0.05%/°C	Maximum load front/back	3600/1600 with safety factor 1.5
		Fire safety class	Class C
		Safety class	Class II

*Remark: Do not connect Fuse in Combiner Box with two or more strings in parallel connection
*Remark: Electrical data in this catalog do not refer to a single module and they are not part of the offer.
They only serve for comparison among different module types.
*Caution: Please be kindly advised that PV modules should be handled and installed by qualified people who have professional skills
and please carefully read the safety and installation instructions before using our PV modules.

PACKAGING CONFIGURATION *

Piece/Box	31
Piece/Container(40'HQ)	682

*Customized packaging is available upon request.